




ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

454.665-454.985/ 459.665-459.985 MHz
Dual Band Cavity Band Pass Filter
Part Number: AE454-459BD1174



<u>Characteristics</u>	<u>Band 1</u>	<u>Band 2</u>	<u>Mechanical</u>	
Center Frequency:	454 MHz	459 MHz	Mounting Method:	12-24 Threaded holes
Passband:	454.665-454.985 MHz	459.665-459.985 MHz		Connectors:
Passband Insertion Loss:	<= 2.0 dB	<= 2.0 dB	Dimensions:	9.46" x 4.81" X 2.88" max
Passband Return Loss:	>=15 dB	>=15 dB		240 x 122 x 73 mm
Input / Output Impedance:	50 Ohms	50 Ohms	<u>Environmental</u>	
Rejection	80 dB @ 449.985 MHz	80 dB @ 464.665 MHz	Operating Temperature:	-10 to +35 deg.C
Power Handling:	50 Watt	50 Watt	Storage Temperature:	-55 to +85 deg.C
			Shock:	20 G. 11 ms
			Vibration:	20 G. 5 to 200 Hz

Outline Drawing:



2 decimal places: +/-0.01 inches [+/- 0.3mm]
3 decimal places: +/- 0.005 inches [+/- 0.13mm]
Angles: +/- 1 Deg.

When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

454.665-454.985/ 459.665-459.985 MHz
Dual Band Cavity Band Pass Filter
Part Number: AE454-459BD1174



Response Plot

