



140 MHz Saw Filter
Part Number: AM140S372



Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	139.85	140.00	140.15
Insertion Loss at Fo	dB	-	22.5	24.0
Passband Ripple Variation	dB	-	0.65	1.00
Group Delay Variation	nsec	-	70	120
Absolute Delay at Fo	usec	-	1.35	-
Bandwidth at 3.0 dB	MHz	20.00	20.30	-
Bandwidth at 40.0 dB	MHz	-	23.85	24.00
Ultimate Attenuation	dB	50	60	-
Substrate Material	128 LiNbO ₃			

Parameters Description	Unit	Minimum	Typical	Maximum
Operation Temperature Range	°C	-30	-	+80
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (Single Ended) ₁	Ω	-	50	-
Load Impedance (Single Ended) ₁	Ω	-	50	-




140 MHz Saw Filter

Part Number: AM140S372



Outline Drawing:



Testing Environment:



Bottom View

Source/Load Impedance = 50 Ω

Ambient Temperature = 25°C



140 MHz Saw Filter

Part Number: AM140S372



Frequency Response:

