



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

463 MHz CDMA 450 H-Band RF-Rx Saw Filter

Part Number: AM463S491




Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	463.5	-
Insertion Loss in 461.3 ~ 465.8 MHz	dB	-	2.2	4.0
VSWR in 461.3 ~ 465.8 MHz	-	-	2.1	2.5
Attenuation:				
0.3 ~ 451.3 MHz	dB	40	55	-
451.3 ~ 455.8 MHz	dB	35	50	-
485.0 ~ 507.5 MHz	dB	40	50	-
507.5 ~ 1200.0 MHz	dB	40	55	-
1200.0 ~ 2000.0 MHz	dB	35	50	-


Parameters Description	Unit	Minimum	Typical	Maximum
Operation Temperature Range	°C	-30	-	+80
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	27
Source Impedance (Single Ended) ₁	Ω	-	50	-
Load Impedance (Single Ended) ₁	Ω	-	50	-
Package Size and Type	3.0 x 3.0 x 1.3 mm		M1	



Outline Drawing:



Testing Environment:





Source Impedance : 50 Ω

Load Impedance : 100 Ω



Response Plot:







ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

463 MHz CDMA 450 H-Band RF-Rx Saw Filter

Part Number: AM463S491



VSWR



Smith Chart

