



AT-THE CENTER FREQUENCY

New Products Announcement from Anatech Electronics

RF and Microwave Filters to mitigate RF interference & communication systems



1500 MHz Low Pass Filter

[AE1500L9118](#)



1526 - 1560 MHz / 1625 - 1662 MHz
Cavity Duplexer

[AE1543-1643DB5161](#)



1574 MHz Waveguide Bandstop Filter

[AE1574WN2218](#)

The AE1500L9118 is a Low Pass filter with SMA Female connectors. This Low Pass filter has a return loss in Passband of 14 dB Min and an insertion loss in Passband of 1.5 dB Max. For more information, [click here](#).

Our AE1543-1643DB5161 is a Cavity Duplexer with SMA Female connectors and has an isolation of 60 dB Min. This Duplexer has an insertion loss of 1.0 dB Max and a return loss of 15 dB Min. For more information, [click here](#).

The AE1574WN2218 is a Waveguide Bandstop filter with SMA Female connectors and has an attenuation of 30 dB Min. This Bandstop filter has an insertion loss of 1.2 dB Max and a VSWR of 1.5:1 Max. For more information, [click here](#).

Visit our website at www.anatechelectronics.com
Can't find what you're looking for? [Click here](#) to get a quote on custom filters to fit your specifications.



(973) 772-4242



Send us an [email](#)